
HEROES WEAR HAIX®





Heel bend



HAIX®-AS System

Upper material: A combination of soft and supple waterproof leather, hydrophobic, breathable (5,0 mg/cm²/h), 2.0 – 2.2 mm thick and nylon fabric

Inner Lining: GORE-TEX® Laminat with XCR® - Product Technology; 3-layer GORE-TEX® laminate, waterproof and highly breathable. Abrasion-resistant lining with optimized- climate comfort, especially for flexible alternating inside and outside use.

Non-woven insole: Non-woven insole absorbs sweat and moisture

Foot bed: Anatomically formed, exchangeable, washable, very good moisture absorption, dries quickly

Sole: Rubber/PU sole with a sporty street/terrain tread. Optimal step and bend behaviour due to sporty toe and heel rounding. The low-weight PU, impact-absorbing wedge ensures outstanding walking characteristics. Oil and gasoline resistant, non-marking. Compliant with EN ISO 20347:2007

HAIX®-Climate-System: Climate System with Micro-Dry lining at the top of the boot leg HAIX®-AS-System: Optimal support and shock absorption in the arch provided by an anatomically formed last. Improved heel and arch design provides support while securing the foot, allowing for increased comfort and range of motion in the spacious toe area

Others: Light weight. Extreme breathable with the combination of fabric and high breathable leather

Sun Reflect: Reduces the heating effect of the upper leather by direct sunlight. Sunlight is reflected by the leather, keeping the leather and the feet cooler.

AIRPOWER® P3

Art.-Nr. 108001

CE EN ISO 20347:2007 02 HI CI HRO WR FO SRC

Leather/textile combination, waterproof and extremely breathable with GORE-TEX® Laminat with XCR®-Product Technology, HAIX®-Climate-System, HAIX®-AS-System, Leg height 19,5 cm, antistatic

Available sizes UK 3 1/2 - 12, Extra large sizes 12 1/2 - 14











HAIX®-Schuhe

Produktions- und Vertriebs GmbH

Auhofstrasse 10, 84048 Mainburg, Germany T. +49 (0) 87 51/86 25-0,

F. +49 (0) 87 51/86 25-25

Email: info@haix.de, Internet: www.haix.com